

**FAN/FIXTURE BOX RATING AND NUMBER OF SINGLE CONDUCTORS**

| CATALOG NUMBER | CUBIC INCHES | UL FAN LOAD RATING (LBS.)      | CSA FAN LOAD RATING (LBS.) | UL FIXTURE STATIC RATING (LBS.) | CSA FIXTURE STATIC RATING (LBS.) | # OF SINGLE CONDUCTORS |     |     |
|----------------|--------------|--------------------------------|----------------------------|---------------------------------|----------------------------------|------------------------|-----|-----|
|                |              |                                |                            |                                 |                                  | #14                    | #12 | #10 |
| F426           | 28.0         | -                              | -                          | 50                              | 50                               | -                      | -   | -   |
| F426F          | 28.0         | -                              | -                          | 50                              | 50                               | -                      | -   | -   |
| FA426          | 20.7         | -                              | -                          | 50                              | 50                               | -                      | -   | -   |
| FB405          | 6.0          | 70                             | 50                         | 200                             | 50                               | 3                      | -   | -   |
| FB4050         | 6.0          | 70                             | 50                         | 200                             | 50                               | 3                      | -   | -   |
| FB407          | 8.0          | 70                             | 50                         | 200                             | 50                               | 4                      | 3   | 3   |
| FB4070         | 8.0          | 70                             | 50                         | 200                             | 50                               | 4                      | 3   | 3   |
| FB412          | 14.4         | 70                             | 50                         | 200                             | 50                               | 7                      | 6   | 5   |
| FB415          | 10.3         | 70                             | 50                         | 200                             | 50                               | 5                      | 4   | 4   |
| FB4150         | 10.3         | 70                             | 50                         | 200                             | 50                               | 5                      | 4   | 4   |
| FB417S         | 20.0         | 70                             | 50                         | 70                              | 50                               | 10                     | 8   | 8   |
| FB417SLP       | 20.0         | 70                             | 50                         | 70                              | 50                               | 10                     | 8   | 8   |
| FB423          | 19.5         | 70                             | 50                         | 200                             | 50                               | 9                      | 8   | 7   |
| FB426          | 16.0         | 70                             | 50                         | 200                             | 50                               | 8                      | 7   | 6   |
| FB426F         | 16.0         | 70                             | 50                         | 200                             | 50                               | 8                      | 7   | 6   |
| FB442          | 13.4         | 70                             | 50                         | 200                             | 50                               | 6                      | 4   | 4   |
| FB442F         | 15.5         | 70                             | 50*                        | 200                             | 50*                              | -                      | -   | -   |
| FB442FD        | 25.0         | 70                             | 50*                        | 200                             | 50*                              | -                      | -   | -   |
| FB443          | 18.3         | 70                             | 50                         | 200                             | 50                               | 8                      | 7   | 7   |
| FB443F         | 18.8         | 70                             | 50*                        | 200                             | 50*                              | -                      | -   | -   |
| FB443FD        | 28.5         | 70                             | 50*                        | 200                             | 50*                              | -                      | -   | -   |
| FB444          | 25.6         | 70                             | 50                         | 200                             | 50                               | 13                     | 11  | 10  |
| FB450          | 14.5         | 70                             | 50                         | 200                             | 50                               | 7                      | 6   | 5   |
| FB900          | 14.5         | 70                             | 50                         | 200                             | 50                               | 7                      | 6   | 5   |
| FBA426         | 21.0         | 70                             | 50                         | 100                             | 50                               | -                      | -   | -   |
| FBB450         | 14.5         | 70                             | 50                         | 200                             | 50                               | -                      | -   | -   |
| FBB900         | 14.5         | 70                             | 50                         | 200                             | 50                               | -                      | -   | -   |
| FBC4225BR      | 21.0         | 70                             | 70                         | 70                              | 70                               | -                      | -   | -   |
| FBC4225W       | 21.0         | 70                             | 70                         | 70                              | 70                               | -                      | -   | -   |
| FBR415F        | 18.3         | 70                             | 50*                        | 200                             | 50*                              | -                      | -   | -   |
| FBR423         | 23.0         | 70 @ 24" o.c.<br>70 @ 16" o.c. | 50                         | 90 @ 24" o.c.<br>150 @ 16" o.c. | 50                               | -                      | -   | -   |
| FBR425F        | 27.3         | 70                             | 50*                        | 200                             | 50*                              | -                      | -   | -   |
| FBR5407R       | 8.0          | 35                             | 50                         | 50                              | 50                               | 4                      | 3   | 3   |
| FBR5415        | 15.6         | 70 @ 24" o.c.<br>70 @ 16" o.c. | 50                         | 90 @ 24" o.c.<br>150 @ 16" o.c. | 50                               | 7                      | 6   | 6   |
| FBR54200R      | 20.0         | 70 @ 24" o.c.<br>70 @ 16" o.c. | 50                         | 70 @ 24" o.c.<br>150 @ 16" o.c. | 50                               | -                      | -   | -   |
| FBR5420R       | 20.0         | 35                             | 50                         | 50                              | 50                               | 10                     | 8   | 8   |
| FBR5420SC      | 20.0         | 70                             | 50                         | 70                              | 50                               | 10                     | 8   | 8   |
| FBS1423*       | 23.0         | 70                             | 50                         | 70                              | 50                               | -                      | -   | -   |
| FBS405         | 6.0          | 70                             | 50                         | 200                             | 50                               | 3                      | -   | -   |
| FBS405T        | 6.0          | 70                             | 50                         | 200                             | 50                               | 3                      | -   | -   |
| FBS407         | 8.0          | 70                             | 50                         | 200                             | 50                               | 4                      | 3   | 3   |
| FBS407T        | 8.0          | 70                             | 50                         | 200                             | 50                               | 4                      | 3   | 3   |

(continued on next page)



**FAN/FIXTURE BOX RATING AND NUMBER OF SINGLE CONDUCTORS**

| CATALOG NUMBER | CUBIC INCHES | UL FAN LOAD RATING (LBS.) | CSA FAN LOAD RATING (LBS.) | UL FIXTURE STATIC RATING (LBS.) | CSA FIXTURE STATIC RATING (LBS.) | # OF SINGLE CONDUCTORS |     |     |
|----------------|--------------|---------------------------|----------------------------|---------------------------------|----------------------------------|------------------------|-----|-----|
|                |              |                           |                            |                                 |                                  | #14                    | #12 | #10 |
| FBS415         | 14.6         | 70                        | 50                         | 200                             | 50                               | 7                      | 6   | 6   |
| FBS415S        | 14.6         | 70                        | 50                         | 70                              | 50                               | 7                      | 6   | 6   |
| FBS420         | 20.0         | 70                        | 50                         | 200                             | 50                               | 10                     | 8   | 8   |
| FBS420S        | 20.0         | 70                        | 50                         | 70                              | 50                               | 10                     | 8   | 8   |
| FBX900         | 14.5         | 70                        | 50                         | 70                              | 50                               | 7                      | 6   | 5   |
| FN430F         | 30.5         | -                         | -                          | 50                              | 50                               | -                      | -   | -   |
| FN440F         | 39.5         | -                         | -                          | 50                              | 50                               | -                      | -   | -   |
| MB8            | 6.1          | 70                        | 50                         | 200                             | 50                               | 3                      | -   | -   |

