




EMT100



EMT400S



EMT200S - EMT400S

Insulating Bushings

Press fit, holds firmly in place while pulling cables. Refer to page I-2 for Rigid Insulating Bushings size 1/2" through 4".



CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	UNIT PKG	STD PKG	DIM A	DIM B
EMT50	12200	1/2	100	1000	.520	.840
EMT75	12205	3/4	100	1000	.531	1.056
EMT100	12220	1	100	100	.625	1.278
EMT125	12225	1-1/4	100	100	.614	1.640
EMT150	12230	1-1/2	100	100	.630	1.915
EMT200	12235	2	50	50	.627	2.327
EMT250*	12240	2-1/2	25	25	1.230	3.065
EMT300*	12245	3	25	25	1.230	3.695
EMT350*	12250	3-1/2	25	25	1.230	4.311
EMT400*	12255	4	25	25	1.240	4.812
Split Insulating Bushings†						
EMT200S	15301	2	50	50	.875	2.327
EMT250S*	12270	2-1/2	25	25	1.240	3.065
EMT300S*	12271	3	25	25	1.240	3.695
EMT350S*	12272	3-1/2	25	25	1.240	4.311
EMT400S*	22001	4	25	25	1.240	4.812

UL E60812 SP LR49636 †PATENTED. MADE IN USA.

*Can also be used for rigid, IMC, and PVC rigid conduit. Note: Meets 2020 NEC code requirements for 300.15(c) protection. Listed for use in environmental air handling spaces per 2020 NEC code requirements 300.22(c).



The new EMT400S insulating bushing is split for easy installation when cables are already in place. They press fit onto conduit and secure with a cable tie. When used for cable protection only, these insulating bushings are a perfect substitution for costly fittings.



Place board over bushing and tap onto Rigid or EMT with hammer.