


SG38AST


SG380AST



SG380AST



SG38AST



SADDLE GRIP® SNAP-TITE® Connectors

For aluminum and steel Flex • AC • AC90 • MCI • MCI-A cable • HCF steel and aluminum cable. Zinc die-cast.

SNAP-TITE® and SNAP2IT® products have been tested and listed by UL in accordance with UL's ground fault requirements. For additional information see page Index-8.

(See page E-1 for ring removal instructions.)

| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | TRADE SIZE | KO SIZE | UNIT PKG | STD PKG | DIM A | DIM B | DIM C | CABLE RANGE | END STOP DIAMETER |
|----------------|--------------------------|------------|---------|----------|---------|-------|-------|-------|-------------|-------------------|
| SG38AST*‡ | 80144 | 3/8 | 1/2 | 50 | 500 | 1.203 | .555 | 1.077 | .405-.612 | .400 |
| SG380AST*‡ | 80148 | 3/8 | 1/2 | 50 | 500 | 1.145 | .555 | 1.077 | .405-.612 | .400 x .580 |
| SG50ST‡ | 80150 | 1/2 | 1/2 | 50 | 500 | 1.458 | .510 | 1.235 | .710-.910 | .620 |
| SG50AST*‡ | 17501 | 1/2 | 1/2 | 50 | 500 | 1.145 | .555 | 1.277 | .710-.910 | .620 |
| SG75ST | 18080 | 3/4 | 3/4 | 20 | 200 | 1.495 | .510 | 1.570 | .840-1.110 | .820 |
| SG75AST* | 17755 | 3/4 | 3/4 | 20 | 200 | 1.540 | .555 | 1.570 | .840-1.110 | .820 |



MADE IN USA.

*Provided with insulated throat. ‡Also for MCI-A cable. See page E-30 and E-31 for MCI-A cable ranges. For cables smaller than 0.405" see L16 on page E-13 and L16ST on page E-5. Refer to chart on page E-27 for list of cable types. Concrete tight when taped.