



Insulated Metal Grounding Bushings

Threaded. With dual rated CU-AL C-clamp grounding lug. Zinc die-cast. 150° C rated.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	GROUND MIN	WIRE MAX	UNIT PKG	STD PKG	DIM A	DIM B	THREADS/ INCH
450	00450	1/2	14	4	25	100	1.896	.458	14
451	00451	3/4	14	4	25	100	2.109	.482	14
452	00452	1	14	4	25	100	2.384	.576	11-1/2
453	00453	1-1/4	14	4	20	80	2.734	.644	11-1/2
453100	01453	1-1/4	14	1/0	20	20	3.214	.644	11-1/2
454	00454	1-1/2	14	2	20	80	3.130	.715	11-1/2
454100	01454	1-1/2	14	1/0	20	20	3.453	.715	11-1/2
455	00455	2	14	2	10	50	3.604	.715	11-1/2
455100	01455	2	14	1/0	10	10	3.927	.715	11-1/2
456	00456	2-1/2	14	2/0	5	20	4.652	.942	8
456250	01456	2-1/2	6	250MCM	10	10	5.042	.942	8
457	00457	3	14	2/0	5	20	4.810	.970	8
457250	01457	3	6	250MCM	10	10	5.200	.970	8
458	00458	3-1/2	14	2/0	5	20	5.783	.969	8
458250	01458	3-1/2	6	250MCM	5	5	6.443	.969	8
459	00459	4	14	2/0	5	20	6.282	.992	8
459250	01459	4	6	250MCM	5	5	6.672	.992	8
4591	04591	5	8	2/0	5	5	7.249	.990	8
4591250	45912	5	2	250MCM	5	5	7.639	.990	8
4592	04592	6	8	2/0	5	5	8.253	1.358	8
4592250	45922	6	2	250MCM	5	5	8.643	1.358	8

  **MADE IN USA.**
E75814 LR49636