

Boxes accommodate 1/2" or 5/8" drywall with 3/4" furring strips or hat channel.

CATALOG NUMBER	UPC/DC/NAED MFG #018997	DESCRIPTION / CU. IN.	UNIT PKG	STD PKG	DIM A	DIM B	DIM C
FB412	72189	Pan box/14.4 cu. in.	25	25	3.000	1.250	4.250
FB423	72190	Press on box/19.5 cu. in.	25	25	3.000	1.250	4.250



**PATENTED.**  
**MADE IN USA.**

**Note: Install fan or fixture (not included) in accordance with manufacturer's instructions and all local applicable electrical codes, using the parked screws provided.** Refer to chart on page R-25 for load ratings and number of single conductors.

## FEATURES AND BENEFITS

- Also for double 5/8" drywall
- No loose parts to misplace, totally self-contained!
- For use with 1/2" or 5/8" drywall with 3/4" furring strips or hat channel
- Attaches securely to joist through shipped in place center screw
- UL rated: 70 lb fan; 200 lb fixture; CSA rated: 50 lb fan/fixture
- 2 hour fire rating

## FAN/FIXTURE BOX INCLUDES

A ready to tighten center screw, installed NM cable connector, mud cover, second KO, and two screws for fan/fixture bracket installation (screwed in place until removed by installer).

