


FBS405T



FBS405

Steel Pan Fan & Fixture Mounting Boxes

Steel box. Ceiling fan/fixture pan boxes mount directly to a joist for a secure installation.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	DESCRIPTION / CU. IN.	UNIT PKG	STD PKG	DIM A	DIM B
FBS405	76185	For 1/2" or 5/8" drywall 6.0 cu. in.	25	25	.570	4.250
FBS407	76187	For 5/8" drywall 8.0 cu. in.	25	25	.680	4.250
FBS405T*	40500	For 1/2" or 5/8" drywall 6.0 cu. in.	25	25	.570	4.250
FBS407T*	40700	For 5/8" drywall 8.0 cu. in.	25	25	.720	4.250



PATENTED.

Note: Install fan or fixture (not included) in accordance with manufacturer's instructions and all local applicable electrical codes, using the parked screws provided. *Fan/fixture mounting bracket attaches to box through threaded openings using provided #10 screws. Refer to chart on page R-26 for load ratings and number of single conductors.

FEATURES AND BENEFITS

- Combination hex/Phillips head screws for easy installation with power screwdrivers
- Fan/fixture installation screws are parked and ready for easy fan/fixture bracket installation!
- UL rated: 70 lb fan, 200 lb fixture; CSA rated: 50 lb fan/fixture
- Protective plastic tips on the installation screws for added safety
- No loose parts to misplace, totally self contained!
- Center screw is shipped in place
- Competitively priced
- Plated steel finish

FAN/FIXTURE BOX INCLUDES

Installation screws, installed NM cable connector, mud cover, additional KO's, and two screws for fan/fixture bracket installation (screwed in place until removed by installer).



INSTALLATION INSTRUCTIONS for FBS405



1 Install FBS405 on joist using shipped in place screw near center of box.



2 Drill (2) 1/8" diameter holes into joist through the elongated openings on each side of box. Remove the (2) long screws noted above to mount the fan/fixture bracket.



3 Mount the fan/fixture bracket into the drilled holes. And you're ready to install the fan or fixture.