

If you have any questions or if parts are missing from your FLBC8530 COVER KIT, please call our Customer Service Department at 1-800-233-4717. Do not call or return this product to your local store or distributor.

## Installation Instructions

- Turn OFF power at MAIN PANEL BOX.
- Remove paper from adhesive side of FLOOR GASKET and adhere to underside of COVER PLATE.
- Install COVER PLATE into GANGABLE FLOOR BOXES (sold separate), tighten (6) #6-32 x 1" SCREWS
- Install COVER PLATE Into GANGABLE FECOR BOXES (sold separate), tighten (b) #0-52 x F SCREWS thru ANGLED FACE of COVER PLATE into FLOOR BOXES. Do not overtighten.
  Wire RECEPTACLES and/or LOW VOLTAGE HOLDERS according to NEC, State and Local codes and attach to COVER PLATE using (6) #6-32 x .5" SCREWS. <u>Note</u>: Place LOW VOLTAGE SPACERS on COVER PLATE ledge below LOW VOLTAGE HOLDERS before attaching screws.
- Place INSERT GASKETS over secured RECEPTACLES and/or LOW VOLTAGE HOLDERS.
- Place INSERT/LID ASSEMBLIES onto INSERT GASKETS and attach with (12) #6-32 x .75" SCREWS.

NOTE: All wiring must be according to NEC, State and Local codes. WARNING: Make sure power is OFF at main panel box before installing. The manufacturer warrants this product for material and workmanship only, and shall not be liable for any special, incidental, or consequential damages or for damages or loss caused by improper use or installation.