

NEW!
more on
reverse

T-Box[®] for Suspended Ceiling Grids

UL Listed • Two Styles • 28.0 cu inch box



**Position EITHER BOX
on the grid
at the Cross...**



...or the Straight




Arlington's new economical **T-Box[®]** is the cost-effective way to mount a fan or fixture on a suspended ceiling grid.

What's neat about *this* T-Box... it can be positioned on the ceiling grid at the cross of the T-rails – or on the straight away so YOU decide where you want the fan/fixture!.

Uses include fans and fixtures of course, but also smoke and carbon monoxide detectors, security cameras, exit signs and emergency lighting.

And they're easy to install! Simply cut around the ceiling tile. Then lower the box into place onto the ceiling grid where it's held securely in place.

For use on premium/reveal edge ceiling tiles, the box height adjusts by removing the tabs with pliers... *easy and convenient!*



- 28.0 cu inch box, available in two styles:
FB428SC with a metal hanger for fans and fixtures up to 70 lbs...
F428SC with a plastic hanger for fixtures (only) up to 50 lbs.
Both include an installed NM cable connector.
- UL Listed
- Meets 2017 NEC, section 314.27 for fan and fixture boxes



Arlington[®]

1 Stauffer Industrial Park
Scranton, PA 18517
800/233.4717 • Fax 570/562.0646
www.aifittings.com

T-Box[®] for Suspended Ceiling Grids

UL Listed • A box for Fans/Fixtures, another for Fixtures Only

FB428SC
Metal
hanger



F428SC
Plastic
hanger



NEW!

CATALOG NUMBER	UPC/DCI/NAED MFG. #018997	DESCRIPTION	UNIT PKG	STD PKG
FB428SC	06911	T-Box with metal hanger for Fans/Fixtures up to 70 lbs Includes Wire Grabber™ with Braided Drop Wire Support Kit, installed NM cable connector, (2) #10-32-32 x 4" screws, grid cover	1	10/ctn
F428SC	06910	T-Box with plastic hanger for Fixtures (ONLY) up to 50 lbs Includes 12 ft. Support Wire Coil, installed NM cable connector, grid cover	1	10/ctn

FB428SC Costs Less than our FBRS420SC for fans and F428SC Costs Less than the FS420SCL for fixtures!

INSTALLATION INSTRUCTIONS

1 Locate position of item to install.

A = straight on T-bar rail.

B = Intersection of T-bar rails (cross).



2 Cut out around ceiling tile.

A = for straight.

B = for cross.



3 Drop box onto grid from overhead.

Remove tabs as necessary to adjust ceiling tile height.




Attach drop wire to structural member. Install NM cable through installed NM connector. Reinstall ceiling tiles.


4 Install fan, fixture or other item per manufacturer's instructions.

FOR FANS/FIXTURES

Install bracket with supplied screws.



FOR FIXTURES Use screws supplied by fixture manufacturer.



Arlington[®]

1 Stauffer Industrial Park
Scranton, PA 18517
800/233.4717 • Fax 570/562.0646
www.aifittings.com

Distributed by