

**FAN/FIXTURE BOX RATING AND NUMBER OF SINGLE CONDUCTORS**

CATALOG NUMBER	CUBIC INCHES	UL FAN LOAD RATING (LBS.)	CSA FAN LOAD RATING (LBS.)	UL FIXTURE STATIC RATING (LBS.)	CSA FIXTURE STATIC RATING (LBS.)	# OF SINGLE CONDUCTORS		
						#14	#12	#10
F426	28.0	-	-	50	50	-	-	-
F426F	28.0	-	-	50	50	-	-	-
FA426	20.7	-	-	50	50	-	-	-
FB405	6.0	70	50	200	50	3	-	-
FB4050	6.0	70	50	200	50	3	-	-
FB407	8.0	70	50	200	50	4	3	3
FB4070	8.0	70	50	200	50	4	3	3
FB412	14.4	70	50	200	50	7	6	5
FB415	10.3	70	50	200	50	5	4	4
FB4150	10.3	70	50	200	50	5	4	4
FB417S	20.0	70	50	70	50	10	8	8
FB417SLP	20.0	70	50	70	50	10	8	8
FB423	19.5	70	50	200	50	9	8	7
FB426	16.0	70	50	200	50	8	7	6
FB426F	16.0	70	50	200	50	8	7	6
FB442	13.4	70	50	200	50	6	4	4
FB442F	15.5	70	50*	200	50*	-	-	-
FB442FD	25.0	70	50*	200	50*	-	-	-
FB443	18.3	70	50	200	50	8	7	7
FB443F	18.8	70	50*	200	50*	-	-	-
FB443FD	28.5	70	50*	200	50*	-	-	-
FB444	25.6	70	50	200	50	13	11	10
FB450	14.5	70	50	200	50	7	6	5
FB900	14.5	70	50	200	50	7	6	5
FBA426	21.0	70	50	100	50	-	-	-
FBB450	14.5	70	50	200	50	-	-	-
FBB900	14.5	70	50	200	50	-	-	-
FBC4225BR	21.0	70	70	70	70	-	-	-
FBC4225W	21.0	70	70	70	70	-	-	-
FBR415F	18.3	70	50*	200	50*	-	-	-
FBR423	23.0	70 @ 24" o.c. 70 @ 16" o.c.	50	90 @ 24" o.c. 150 @ 16" o.c.	50	-	-	-
FBR425F	27.3	70	50*	200	50*	-	-	-
FBR5407R	8.0	35	50	50	50	4	3	3
FBR5415	15.6	70 @ 24" o.c. 70 @ 16" o.c.	50	90 @ 24" o.c. 150 @ 16" o.c.	50	7	6	6
FBR54200R	20.0	70 @ 24" o.c. 70 @ 16" o.c.	50	70 @ 24" o.c. 150 @ 16" o.c.	50	-	-	-
FBR5420R	20.0	35	50	50	50	10	8	8
FBR5420SC	20.0	70	50	70	50	10	8	8
FBS1423*	23.0	70	50	70	50	-	-	-
FBS405	6.0	70	50	200	50	3	-	-
FBS405T	6.0	70	50	200	50	3	-	-
FBS407	8.0	70	50	200	50	4	3	3
FBS407T	8.0	70	50	200	50	4	3	3

(continued on next page)



**FAN/FIXTURE BOX RATING AND NUMBER OF SINGLE CONDUCTORS**

CATALOG NUMBER	CUBIC INCHES	UL FAN LOAD RATING (LBS.)	CSA FAN LOAD RATING (LBS.)	UL FIXTURE STATIC RATING (LBS.)	CSA FIXTURE STATIC RATING (LBS.)	# OF SINGLE CONDUCTORS		
						#14	#12	#10
FBS415	14.6	70	50	200	50	7	6	6
FBS415S	14.6	70	50	70	50	7	6	6
FBS420	20.0	70	50	200	50	10	8	8
FBS420S	20.0	70	50	70	50	10	8	8
FBX900	14.5	70	50	70	50	7	6	5
FN430F	30.5	-	-	50	50	-	-	-
FN440F	39.5	-	-	50	50	-	-	-
MB8	6.1	70	50	200	50	3	-	-

